

E-LIQUIDE 50/50 SALT E-VAPOR USA STRONG 20 MG/ML - SEV-USASTRG-20

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : E-LIQUIDE 50/50 SALT E-VAPOR USA STRONG 20 MG/ML

Product code : SEV-USASTRG-20.

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Registered company name : LABORATOIRE LIPS FRANCE.

Address : PA DU BIGNON.44110.ERBRAY.FRANCE.

Telephone : 02 40 28 71 67. Fax : .

contact@lefrenchliquide.com

www.lipsfrance.com

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Acute oral toxicity, Category 3 (Acute Tox. 3, H301).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

May produce an allergic reaction (EUH208).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS06

Signal Word :

DANGER

Product identifiers :

EC 200-193-3 NICOTINE (ISO)

Additional labeling :

EUH208 Contains CINNAMIC ALDEHYDE *. May produce an allergic reaction.

Hazard statements :

H301 Toxic if swallowed.

H319 Causes serious eye irritation.

Precautionary statements - General :

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

Precautionary statements - Prevention :

P264 Wash ... thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response :

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/...

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

E-LIQUIDE 50/50 SALT E-VAPOR USA STRONG 20 MG/ML - SEV-USASTRG-20

P330	Rinse mouth.
P337 + P313	If eye irritation persists: Get medical advice/attention.
Precautionary statements - Storage :	
P405	Store locked up.
Precautionary statements - Disposal :	
P501	Dispose of contents/container to ...

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures****Composition :**

Identification	(EC) 1272/2008	Note	%
CAS: 56-81-5 EC: 200-289-5 GLYCEROL		[1]	25 \leq x % < 50
CAS: 57-55-6 EC: 200-338-0 REACH: 01-2119456809-23 PROPYLENE GLYCOL		[1]	25 \leq x % < 50
CAS: 54-11-5 EC: 200-193-3 NICOTINE (ISO)	GHS06, GHS09 Dgr Acute Tox. 1, H300 Acute Tox. 2, H310 Acute Tox. 2, H330 Aquatic Chronic 2, H411	[1]	1 \leq x % < 2.5
CAS: 79-33-4 EC: 201-196-2 L-LACTIC ACID	GHS05 Dgr Skin Irrit. 2, H315 Eye Dam. 1, H318		1 \leq x % < 2.5
CAS: 104-55-2 EC: 203-213-9 CINNAMIC ALDEHYDE *	GHS07 Wng Acute Tox. 4, H312 Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1A, H317		0 \leq x % < 1

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures**In the event of exposure by inhalation :**

In the event of an allergic reaction, seek medical attention.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

In the event of splashes or contact with skin :

In the event of an allergic reaction, seek medical attention.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water, administer activated medical charcoal and consult a doctor.

Seek medical attention, showing the label.

E-LIQUIDE 50/50 SALT E-VAPOR USA STRONG 20 MG/ML - SEV-USASTRG-20

If swallowed accidentally, do not allow to drink, do not induce vomiting and transfer to hospital immediately by ambulance. Show the label to the doctor.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

If the ground is contaminated, once the product has been recovered by sponging with an inert and non-combustible absorbent material, wash the contaminated area in plenty of water.

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Fire prevention :

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid eye contact with this mixture.

Avoid exposure - obtain special instructions before use.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

E-LIQUIDE 50/50 SALT E-VAPOR USA STRONG 20 MG/ML - SEV-USASTRG-20**Storage**

Keep out of reach of children.

Keep away from food and drink, including those for animals.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters****Occupational exposure limits :**

- European Union (2017/164/UE, 2009/161/UE, 2006/15/CE, 2000/39/CE, 98/24/CE)

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Notes :
54-11-5	0,5	-	-	-	Peau

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
56-81-5	10 mg/m3				
54-11-5	0,5 mg/m3			Skin	

- Germany - AGW (BAuA - TRGS 900, 21/06/2010) :

CAS	VME :	VME :	Excess	Notes
54-11-5		0,5 mg/m3		2(II)

- France (INRS - ED984 :2012) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
56-81-5	-	10	-	-	-	-
54-11-5	-	0.5	-	-	-	-

- UK / WEL (Workplace exposure limits, EH40/2005, 2007) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
56-81-5	10 mg/m3				
57-55-6	150 ppm 474 mg/m3				
54-11-5	0,5 mg/m3	1,5 mg/m3		Sk	

Predicted no effect concentration (PNEC):

PROPYLENE GLYCOL (CAS: 57-55-6)

Environmental compartment: PNEC :	Soil. 50 mg/kg
Environmental compartment: PNEC :	Fresh water. 260 mg/l
Environmental compartment: PNEC :	Sea water. 26 mg/l
Environmental compartment: PNEC :	Intermittent waste water. 183 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 572 mg/kg
Environmental compartment: PNEC :	Marine sediment. 57.2 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 20000 mg/l
Environmental compartment: PNEC :	Fresh water predators (oral). 1133 mg/kg

E-LIQUIDE 50/50 SALT E-VAPOR USA STRONG 20 MG/ML - SEV-USASTRG-20**8.2. Exposure controls****Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVC (polyvinyl chloride)
- Butyl Rubber (Isobutylene-isoprene copolymer)

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties****General information :**

Physical state : Fluid liquid.

Important health, safety and environmental information

pH : Not stated.

Neutral.

Boiling point/boiling range : Not specified.

Flash Point Interval : FP > 100°C.

Vapour pressure (50°C) : Not relevant.

Density : > 1

Water solubility : Soluble.

Viscosity: $v < 7 \text{ mm}^2/\text{s}$ (40°C)

Melting point/melting range : Not specified.

Self-ignition temperature : Not specified.

Decomposition point/decomposition range : Not specified.

9.2. Other information

No data available.

E-LIQUIDE 50/50 SALT E-VAPOR USA STRONG 20 MG/ML - SEV-USASTRG-20**SECTION 10 : STABILITY AND REACTIVITY****10.1. Reactivity**

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid :

- frost

10.5. Incompatible materials**10.6. Hazardous decomposition products**

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects**

Toxic if swallowed.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

11.1.1. Substances**Acute toxicity :**

CINNAMIC ALDEHYDE * (CAS: 104-55-2)

Oral route : LD50 = 2500 mg/kg

L-LACTIC ACID (CAS: 79-33-4)

Oral route : LD50 = 3450 mg/kg

NICOTINE (ISO) (CAS: 54-11-5)

Oral route : LD50 = 5 mg/kg
Species : Rat

Dermal route : LD50 = 70 mg/kg
Species : Rabbit

Inhalation route (Dusts/mist) : LC50 = 0.19 mg/l
Species : Rat

PROPYLENE GLYCOL (CAS: 57-55-6)

Oral route : LD50 > 2000 mg/kg
Species : Rat

Dermal route : LD50 = 20800 ml/kg
Species : Rabbit

11.1.2. Mixture**Respiratory or skin sensitisation :**

Contains at least one sensitising substance. May cause an allergic reaction.

SECTION 12 : ECOLOGICAL INFORMATION**12.1. Toxicity****12.1.1. Substances**

NICOTINE (ISO) (CAS: 54-11-5)

Fish toxicity : LC50 = 4 mg/l
Species : Oncorhynchus mykiss

E-LIQUIDE 50/50 SALT E-VAPOR USA STRONG 20 MG/ML - SEV-USASTRG-20

	Duration of exposure : 96 h
Algae toxicity :	ECr50 = 37 mg/l Species : <i>Desmodesmus subspicatus</i> Duration of exposure : 72 h
PROPYLENE GLYCOL (CAS: 57-55-6) Fish toxicity :	LC50 = 51400 mg/l Species : <i>Pimephales promelas</i> Duration of exposure : 96 h
Crustacean toxicity :	EC50 = 34400 mg/l Species : <i>Daphnia magna</i> Duration of exposure : 48 h
Algae toxicity :	NOEC < 5300 mg/l Species : <i>Skeletonema costatum</i> Duration of exposure : 14 days

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability**12.2.1. Substances**

NICOTINE (ISO) (CAS: 54-11-5)

Biodegradability :

no degradability data is available, the substance is considered as not degrading quickly.

PROPYLENE GLYCOL (CAS: 57-55-6)

Chemical oxygen demand :

DCO = 1.63 g/g

Five-day biochemical oxygen demand :

DBO5 = 1.08 g/g

Biodegradability :

Rapidly degradable.
DBO5/DCO = 0.66

12.3. Bioaccumulative potential**12.3.1. Substances**

NICOTINE (ISO) (CAS: 54-11-5)

Octanol/water partition coefficient :

log K_{ow} = 1.17

PROPYLENE GLYCOL (CAS: 57-55-6)

Octanol/water partition coefficient :

log K_{ow} = -0.30

Bioaccumulation :

BCF = 1.4

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

E-LIQUIDE 50/50 SALT E-VAPOR USA STRONG 20 MG/ML - SEV-USASTRG-20**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2017 - IMDG 2016 - ICAO/IATA 2017).

14.1. UN number

3144

14.2. UN proper shipping name

UN3144=NICOTINE COMPOUND, LIQUID, N.O.S. or NICOTINE PREPARATION, LIQUID, N.O.S.
(cinnamic aldehyde *)

14.3. Transport hazard class(es)

- Classification :



6.1

14.4. Packing group

III

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	6.1	T1	III	6.1	60	5 L	43 274	E1	2	E

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	6.1	-	III	5 L	F-A,S-A	43 223 274	E1

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	6.1	-	III	655	60 L	663	220 L	A3 A4 A6	E1
	6.1	-	III	Y642	2 L	-	-	A3 A4 A6	E1

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****- Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2016/1179. (ATP 9)

- Container information:

The mixture is packed in an interior packaging, not exceeding 10 ml, the required labelling elements appear on the outer packaging.

Packaging to be fitted with child-resistant fastenings (see EC Regulation No. 1272/2008, Annex II, Part 3).

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

- Particular provisions :

No data available.

15.2. Chemical safety assessment

E-LIQUIDE 50/50 SALT E-VAPOR USA STRONG 20 MG/ML - SEV-USASTRG-20

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H300	Fatal if swallowed.
H310	Fatal in contact with skin.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H411	Toxic to aquatic life with long lasting effects.

Abbreviations :

PNEC : Predicted No-Effect Concentration

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS06 : Skull and crossbones

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.