

# Test Report

Report No.: ELE2501C00028-A

Date: Apr. 15, 2025

Page No.: 1 of 7

Applicant: Shenzhen Smoore Technology Limited  
Address: No.16, Dongcai Industry Park, Gushu village, Xixiang Town, Bao'An District,  
Shenzhen, China

The following sample was submitted and identified by/on behalf of the client as:

Product Name: DOJO BLAST10K Refill Container(8ml) / DOJO BLAST15000 Refill Container(8ml)  
Flavour: Blueberry raspberry  
Nicotine Conc.: 20mg/mL  
E-liquid Bottle Volume: 8.0 mL  
Trade Mark: DOJO  
Sample Received Date: 2025.1.2  
Testing Period: 2025.1.2—2025.1.8  
Test Method: Please refer to the following page(s).  
Test Result(s): Please refer to the following page(s).  
Remark: Test data of this report was extracted from report No. ELE2501C00008-A.  
The report is to supersede test report ELE2501C00028.

Test Items	Test Requested
1 Carbonyl Compounds: Formaldehyde, Acetaldehyde, Acrolein, Crotonaldehyde	Emission testing according to Article 20 of Tobacco Product Directive (2014/40/EU) & UK Statutory Instruments on The Tobacco and Related Products Regulations 2016, PART 6- Electronic cigarettes.
2 Metals: Aluminum, Chromium, Iron, Nickel, Tin, Lead, Cadmium, Arsenic, Antimony, Mercury, Copper	
3 Nicotine and consistency	
4 Diacetyl and Pentane 2,3 Dione	
5 Ethylene Glycol and Diethylene Glycol	
6 Specific Nitrosamines: N-nitrosornicotine (NNN), 4-(N-methylnitrosamino)-1-(3-pyridyl)-1-butanone (NNK)	
7 VOC substances: Toluene, Benzene, 1,3-Butadiene, Isoprene	

Signed for and on behalf of  
**Shenzhen Element Testing Co., Ltd.**



Noel Yin  
Technical Manager



# Test Report

Report No.: ELE2501C00028-A

Date: Apr. 15, 2025

Page No.: 2 of 7

## Test Results

With reference to Afnor standardization XP D90-300-3:2021, a vaping robot was used to collect the vapor.

puff/vaporisation duration	3.0 s±0.1 s
puffs period	30 s±0.5 s
number of puffs per series	20
Time between 2 series	300 s±120 s
volume for generation of a puff	55 mL±0.3 mL
maximum flow rate	18.3 mL/s±1.8 mL/s
head loss excluding trapping	< 1000 Pa±50 Pa
Number of series	5
total number of puffs	100
total vaporisation duration	300 s
puff profile	square profile

The temperature of the atmosphere was kept between 15 °C and 25 °C and the relative humidity between 40 % and 70 %. The variation in temperature and relative humidity of the test atmosphere during the preparation and testing of the machine was kept within the following limits: temperature ±2°C, relative humidity ±5%.

### 1. Carbonyl Compounds Result(s)

Method: According to Afnor XP D90-300-3:2021 Annex A.5, the aerosol generated by the e-cigarette is absorbed by the impactor containing 40mL acidified solution of 2,4-dinitrophenylhydrazine (DNPH) in acetonitrile. The solution was filtered and analyzed by reverse phase high-performance liquid chromatography and determined using a DAD detector.

Test Item	CAS No.	Unit	LOD	LOQ	Result(s)
Formaldehyde	50-00-0	ng/mg	2.80	8.40	ND
Acetaldehyde	75-07-0	ng/mg	1.77	5.30	2.90
Acrolein	107-02-8	ng/mg	0.17	0.50	ND
Crotonaldehyde	123-73-9	ng/mg	2.38	7.15	ND

- Note:
- ng = nanogram
  - mg= milligram
  - ND = Not Detected (lower than LOD)
  - LOD = Limit of Detection
  - LOQ = Limit of Quantitation
  - “ng/mg”, the amount of each test item in “ng” obtained by instrument analysis dividing the mass of vaporized liquid of 100 puffs in “mg” obtained by weighing

# Test Report

Report No.: ELE2501C00028-A

Date: Apr. 15, 2025

Page No.: 3 of 7

## 2. Metals Result(s)

Method: According to Afnor XP D90-300-3:2021 Annex A.6, the aerosol produced by the e-cigarette is absorbed by the impactor containing 20 mL nitric acid solution. The solution was filtered and analyzed by ICP-MS.

Test Item	CAS No.	Unit	LOD	LOQ	Result(s)
Chromium (Cr)	7440-47-3	ng/mg	0.050	0.151	ND
Nickel (Ni)	7440-02-0	ng/mg	0.044	0.133	0.215
Iron (Fe)	7439-89-6	ng/mg	0.193	0.578	ND
Aluminum (Al)	7429-90-5	ng/mg	0.211	0.632	ND
Tin (Sn)	7440-31-5	ng/mg	0.103	0.308	ND
Lead (Pb)	7439-92-1	ng/mg	0.043	0.130	ND
Cadmium (Cd)	7440-43-9	ng/mg	0.035	0.104	ND
Arsenic (As)	7440-38-2	ng/mg	0.060	0.180	ND
Antimony (Sb)	7440-36-0	ng/mg	0.035	0.104	ND
Mercury (Hg)	7439-97-6	ng/mg	0.051	0.153	ND
Copper (Cu)	7440-50-8	ng/mg	0.035	0.104	ND

- Note:
- ng = nanogram
  - mg = milligram
  - ND = Not Detected (lower than LOD)
  - LOD = Limit of Detection
  - LOQ = Limit of Quantitation
  - "ng/mg", the amount of each test item in "ng" obtained by instrument analysis dividing the mass of vaporized liquid of 100 puffs in "mg" obtained by weighing

# Test Report

Report No.: ELE2501C00028-A

Date: Apr. 15, 2025

Page No.: 4 of 7

### 3. Nicotine and Consistency Test

Method: According to Afnor XP D90-300-3:2021 Annex A.3, wipe the clamp with isopropyl alcohol. Let stand for a minute. The aerosol produced by the e-cigarette is absorbed by the Cambridge filter. Remove the Cambridge filter and place it into a centrifuge tube, add 20 mL of Isopropyl alcohol and 0.2mL internal standard stock solution. Shaken at 210 rpm for 30 min, and the solution was filtered and analyzed by GC-FID.

Test Item	Nicotine (CAS No.:54-11-5) emission (mcg/mg)				Entrapment Efficiency (%)	mcg /puff
	Series 1*	Series 3*	Series 5*	AVG		
Value	14.5	14.5	14.3	14.4	91.1	231
Deviation (%)	0.7	0.7	0.7	-	-	-

- Note:
- mcg = microgram
  - mg = milligram
  - ND = Not Detected (lower than LOD)
  - LOD = Limit of Detection =1.45 mcg/mg
  - LOQ = Limit of Quantitation = 4.35 mcg/mg
  - 1 series = 20puffs
  - \* Values used for determination of consistency of nicotine emission
  - Under the conditions of the test and with reference to AFNOR XP D90-300-3:2021, the electronic cigarette delivers a dose of nicotine at consistent levels.
  - “mcg/mg”, the amount of each test item in “mcg” obtained by instrument analysis dividing the mass of vaporized liquid of 20 puffs in “mg” obtained by weighing.
  - <sup>△</sup> Nicotine content of liquid is tested with reference to Afnor XP D90-300-2:2021 Annex A.4, with the LOQ of 0.0005 mg/mL, is involved in the calculation of entrapment efficiency.
  - The entrapment efficiency is calculated as the ratio between the amount of nicotine measured in the emissions and the amount of nicotine theoretically vaporized. Theoretically vaporized nicotine is determined from the mass of liquid vaporized and the nicotine content in the liquid.

# Test Report

Report No.: ELE2501C00028-A

Date: Apr. 15, 2025

Page No.: 5 of 7

## 4. Diacetyl and Pentane 2,3 Dione Result(s)

Method: According to Afnor XP D90-300-3:2021 Annex A.4, the aerosol produced by the e-cigarette is absorbed by the impactor containing 20mL ethanol. The solution was filtered and analyzed by GC-MS.

Test Item	CAS No.	Unit	LOD	LOQ	Result(s)
Diacetyl	431-03-8	ng/mg	6.3	18.9	ND
Pentane 2,3 Dione	600-14-6	ng/mg	12.6	37.7	ND

- Note:
- ng = nanogram
  - mg = milligram
  - ND = Not Detected (lower than LOD)
  - LOD = Limit of Detection
  - LOQ = Limit of Quantitation
  - “ng/mg”, the amount of each test item in “ng” obtained by instrument analysis dividing the mass of vaporized liquid of 100 puffs in “mg” obtained by weighing

## 5. Ethylene Glycol and Diethylene Glycol Result(s)

Method: With reference to In House Method, wipe the clamp with isopropyl alcohol. Let stand for a minute. 20 mL of methanol was added to the impactor connected in series with the Cambridge filter to absorb the aerosol. The Cambridge filter was removed and placed in methanol, shaken at 210 rpm for 30 min, and then the solution was filtered and analyzed by GC-FID.

Test Item	CAS No.	Unit	LOD	LOQ	Result(s)
Ethylene Glycol	107-21-1	ng/mg	13.0	39.0	ND
Diethylene Glycol	111-46-6	ng/mg	15.8	47.5	ND

- Note:
- ng = nanogram
  - mg = milligram
  - ND = Not Detected (lower than LOD)
  - LOD = Limit of Detection
  - LOQ = Limit of Quantitation
  - “ng/mg”, the amount of each test item in “ng” obtained by instrument analysis dividing the mass of vaporized liquid of 100 puffs in “mg” obtained by weighing

# Test Report

Report No.: ELE2501C00028-A

Date: Apr. 15, 2025

Page No.: 6 of 7

## 6. Specific Nitrosamines Result(s)

Method: According to CORESTA Recommended Method No. 75(2022), the aerosol produced by the e-cigarette is absorbed by the impactor containing 20 mL of 100 mM ammonium acetate solution. The solution was filtered and analyzed by LC-MS/MS.

Test Item	CAS No.	Unit	LOD	LOQ	Result(s)
N-nitrosornicotine (NNN)	80508-23-2	ng/mg	0.48	1.44	ND
4-(N-methylnitrosamino)-1-(3-pyridyl)-1-butanone (NNK)	64091-91-4	ng/mg	0.48	1.44	ND

Note:

- ng = nanogram
- mg = milligram
- ND = Not Detected (lower than LOD)
- LOD = Limit of Detection
- LOQ = Limit of Quantitation
- “ng/mg”, the amount of each test item in “ng” obtained by instrument analysis dividing the mass of vaporized liquid of 100 puffs in “mg” obtained by weighing

## 7. VOC substances Result(s)

Method: According to CORESTA Recommended Method No.70(2019), wipe the clamp with isopropyl alcohol. Let stand for a minute. 20 mL of methanol was added to the impactor connected in series with the Cambridge filter to absorb the aerosol. The Cambridge filter was removed and placed in methanol, shaken at 210 rpm for 30 min, and then the solution was filtered and analyzed by GC-MS.

Test Item	CAS No.	Unit	LOD	LOQ	Result(s)
Toluene	108-88-3	ng/mg	1.67	5.01	ND
Benzene	71-43-2	ng/mg	1.67	5.01	ND
1,3-Butadiene	106-99-0	ng/mg	1.67	5.01	ND
Isoprene	78-79-5	ng/mg	1.67	5.01	ND

Note:

- ng = nanogram
- mg = milligram
- ND = Not Detected (lower than LOD)
- LOD = Limit of Detection
- LOQ = Limit of Quantitation
- “ng/mg”, the amount of each test item in “ng” obtained by instrument analysis dividing the mass of vaporized liquid of 100 puffs in “mg” obtained by weighing

## Test Report

Report No.: ELE2501C00028-A

Date: Apr. 15, 2025

Page No.: 7 of 7

Photo(s) of the sample(s)



**\*\*\* End of Report \*\*\***

*Remark: This report is considered invalidated without the Special Seal of Shenzhen Element Testing Co., Ltd.. This report shall not be altered, increased, or deleted. The results shown in this test report refer only to the sample(s) tested. Without written approval of Shenzhen Element Testing Co., Ltd., this test report shall not be copied except in full and published as advertisement.*